



The 60T has a pulling capacity of 120,000 lbs. The hoist is designed for fast and easy setup by means of a self supporting mast with two 6" bore hydraulic cylinders. A guy cable system is not needed in most situations.



Controls are conveniently located at the left rear corner of the machine in close proximity to the work area.

The front portion of the deck remains completely open for cargo.



Both the mainline and optional sandline use motors that are hydrostatically driven with infinite variable speed control for exceptionally smooth operation. These motors include an internal braking system.

Standard specifications

- Standard mast height: 44 ft.
- Standard layback: 6 ft.
- Capacity with 8-part line: 120,000 lbs.
- Sandline capacity: 13,000 lbs.
- Mainline speed: 38 ft./min
- Sandline speed: 300 ft./min
- Tailout capacity: 3,000 lbs.
- Tailout speed: 100 ft./min.

Standard features

- Internal failsafe brake
- Oil cooler
- Tailout winch
- Rear outriggers with holding valve
- Holding valve on mast cylinders
- Line block with hook
- Electronic walking beam
- Gray paint on Mast / Black on deck

Optional features

- Sandline winch
- Two Speed winch motor
- Breakout wrench
- Front hydraulic outriggers
- Custom paint color
- Tailgate
- Tool boxes
- Mast lights
- Cathead
- Other options available upon request



Hunke Manufacturing LLC

PO Box 128 • Snyder, NE 68664
 Phone: 402-568-2221 • Fax: 402-568-2223
 E-mail: sales@hunkemfg.com • Website: www.hunkemfg.com